

Black annealed steel wire COIL

· Special baling wire (black annealed wire) for balers with automatic bending (cardboard, paper, plastics PET, PHD).

· Drawn wire according to UNE-10016/2 norm and annealed according to UNE-EN 10218 norm. Certified ISO 9001:2000.

Composición química (%):

C: 0,06 máx.
Mn: 0,30 – 0,60
Si: 0,20 máx.
P: 0,035 máx.
S: 0,035 máx.

Spec. Proof strength: 34-41 kg/mm²
Elongation (%): Min. 38-40%

Also available:

- Superior
- In high tensile C1018



Coil dimensions

Ø (mm)	Peso	Ø Interior	Ø Exterior	h
2,4 mm – 4 mm	200 kg	415 mm	850 mm	300 mm
2,7 mm – 4 mm	500 kg	415 mm	850 mm	400 mm
2,7 mm – 4 mm	750 kg	415 mm	850 mm	650 mm
2,7 mm – 4 mm	1000 kg	415 mm	850 mm	800 mm

Sizes and weights

Ø Wire (mm)	Meters in 1 kg.	Grams. in 1 m.
2,40	28,16	35,50
2,70	22,25	44,90
3,00	18,02	55,50
3,20	15,84	63,10
3,40	14,03	71,30
3,70	11,85	84,40
3,80	11,23	89,00
3,90	10,66	93,80



Exel Fil, S.A.
Apdo. de Correos 129
Polígono Industrial s/n
25200 Cervera (Spain)
Tel. + (34) 97 353 22 12
Fax + (34) 97 353 28 09
exelfil@exelfil.com
www.exelfil.com

Sales office / Export
Ganduxer, 127 bajos
08022 Barcelona (Spain)
Tel. + (34) 93 253 17 22
Fax + (34) 93 253 05 83
export@exelfil.com
www.exelfil.com